



EC TYPE EXAMINATION (MODULE B)
CERTIFICATE No. MED599125CS

***This is to certify** that RINA Services S.p.A. (Notified Body No. 0474) did undertake the relevant type approval procedures for the equipment identified below, which was found to be in compliance with the Life-Saving appliances requirements of Marine Equipment Directive (MED) 2014/90/EU, including the requirements and testing standards of Regulation (EU) 2025/1533.*

MED Item N°

MED/1.12

Description

Inflatable liferafts

Type

DEEP-SEA II 6-8-10-12-16-20-25P

Applicant

LALIZAS ITALIA S.R.L.

VIA FONTANELLE 22

16012 Busalla (GE)

ITALY

Testing standards

IMO Res. MSC.81 (70), as amended; IMO Res. MSC.481(102)

Reference standards

**SOLAS 74 Reg. III/13, SOLAS 74 Reg. III/21, SOLAS 74 Reg. III/26,
SOLAS 74 Reg. III/31, SOLAS 74 Reg. III/34, IMO Res. MSC.36(63)-(1994
HSC Code) 8, IMO Res. MSC.48(66)-(LSA Code) I, IMO Res.
MSC.48(66)-(LSA Code) IV, IMO Res. MSC.97(73)-(2000 HSC Code) 8,
IMO Res. MSC.481(102), IMO MSC/Circ.811, IMO MSC.1/Circ.1630 Rev.2.**

Issued in Genoa on
January 19, 2026

This Certificate is valid until
January 18, 2031

This Certificate consists of this sheet plus an attachment

Fabio Morbioni

RINA Services S.p.A.



**ATTACHMENT TO
CERTIFICATE No. MED599125CS**

Page 1 of 3

Manufacturer

LALIZAS ITALIA S.R.L.

Place of Manufacturer

SITE 1: VIA BENEFICIO II TRONCO 57/A

48015 Cervia (RA) ITALY

SITE 2: URSA 14

SINI VIR DISTRICT - PC 2309 PERNIK - BULGARIA

Product description

Throw overboard inflatable liferafts with the following main characteristics:

	DEEP-SEA 6p	DEEP-SEA 8p	DEEP-SEA 10p	DEEP-SEA 12p
Shape	square			
Length/width	1994 mm	2272 mm	2550 mm	2692 mm
Diameter of buoyancy tubes	241 mm	256 mm	270 mm	286 mm
Working pressure	0.017 Mpa			
Type of container /material	Flat : ABS or VTR Roll: VTR			
Maximum weight	Pack A: 84 Kg Pack B:70.5 Kg	Pack A: 98 Kg Pack B: 76 Kg	Pack A: 105.5 Kg Pack B: 81 Kg	Pack A: 117.5 Kg Pack B: 91.5 Kg
Maximum installation height (*)	25 m			
Required towing force	2 kts: 0.5 kN 3 kts: 1.10 kN	2 kts: 0.65 kN 3 kts: 1.25 kN	2 kts: 0.6 kN 3 kts: 1.12 kN	2 kts: 0.75 kN 3 kts: 1.55 kN

	DEEP-SEA 16p	DEEP-SEA 20p	DEEP-SEA 25p
Shape	octogonal		
Length/width	3376 mm / 3376 mm	4280 mm / 4280 mm	4280 mm / 4280 mm
Diameter of buoyancy tubes	320 mm	360 mm	360 mm
Working pressure	0.017 Mpa		
Type of container /material	Roll: VTR		
Maximum weight	Pack A: 153 Kg Pack B: 109 Kg	Pack A: 169 Kg Pack B: 125 Kg	Pack A: 178 Kg Pack B: 125 Kg
Maximum installation height	25 m		
Required towing force	2 kts: 0.8 kN 3 kts: 1.90 kN	2 kts: 1.10 kN 3 kts: 2.18 kN	2 kts: 1.10 kN 3 kts: 2.18 kN

(*) In case of ABS flat container, the maximum installation height is reduced to 18 m.

**ATTACHMENT TO
CERTIFICATE No. MED599125CS**

Page 2 of 3

Coated fabrics:

1. Buoyancy chamber, bottom and canopy support: polyester fabric coated with PVC on both sides 1100Dtex 640 g/m² black or orange colored;
2. External canopy: polyester fabric coated with PVC on both sides 550 Dtx 510 g/m² orange colored or nylon fabric 210/210 2PU WR orange colored;
3. Inner canopy: Nylon fabric coated with polyurethane 2PU+WR 65g/m² light blue colored or Pam 100%+60g/m² light blue colored.

Reference documents

- Technical Specification drawing n°402 Rev 2 issued by Lalizas Italia SRL and approved by RINA with n° CSST 18959;
- Liferaft General arrangement drawings issued by Lalizas Italia Srl and approved by RINA with n° CSST 18954 (OMO-Z-5011-12-13-14) and CSST 18953 (OMO-Z-5015-32-16);
- Canopy Int/Ext General arrangement drawings n° OMO-Z-5026-27-28-29 issued by Lalizas Italia Srl and approved by RINA with n° CSST 18952 (OMO-Z-5026-27-28-29) and CSST 18951 (OMO-Z-5030-33-31);
- Marking details trade mark Arimar/Lalizas Container for Inflatable liferafts particular issued by Lalizas Italia Srl and approved by RINA with n° CSST 18955;
- Marking details trade mark Arimar/Lalizas Inflatable liferafts particular issued by Lalizas Italia Srl and approved by RINA with n° CSST 18956;
- Container Flat Type ABS/GRP n° OMO-Z-5125/5135/5136 and Roll Type VTR n° OMO-Z-5145 approved with n° CSST 24135.

Tests carried out


- Practical test report issued in compliance with MSC.81(70) and MSC.295(87), issued by Arimar Spa, witnessed and filed by RINA with n° CSST 8038 (2011CS013227);
- Inflation system approved and tested in compliance with ISO 15738:2019 (Type Approval FPE164324CS);
- Fabric test report list for inflatable tube fabric, external canopy and internal canopy, issued by Arimar Spa witnessed and filed by RINA with n° CSST 8039 (2011CS013227);
- Practical test report additional in compliance with MSC.81(70) and MSC.295(87), issued by Lalizas Italia Srl, witnessed and filed by RINA with n° CSST 18960 (2020CS013388).
- Inflation test, dated 11/12/2025, witnessed and filed by RINA with n° CSST 25665.

This certificate annuls and replaces the certificate No. MED066925CS dated 02/17/2025.



**ATTACHMENT TO
CERTIFICATE No. MED599125CS
Page 3 of 3**

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production control phase module (D, E or F) of Annex II of the Directive is fully complied with a written inspection agreement with a Notified Body



XXXX/YYYY

"WHEELMARK FORMAT"

*XXXX Notified Body number undertaking surveillance module
YYYY The year in which the mark is affixed*

General conditions for the approval

- a) The initial conditions verified by RINA at the time of the approval are to be maintained
- b) Any changes to the initial conditions are to be promptly communicated to RINA, which reserves the right to repeat the relevant assessment
- c) This certificate will not be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with RINA
- d) RINA personnel are to be allowed to witness during the performances of activities, upon their request
- e) The activities are to be carried out in compliance with the RINA Rules and/or other applicable Rules
- f) Should the specified regulations or standards be amended during the validity of this certificate, the product is to be reapproved prior to it being placed on board vessels to which the amended regulations or standards apply.

Fabio Morbioni

RINA Services S.p.A.